

DISCLOSURE STATEMENT

We are not responsible and provide no warranty on material from Central LA Metal Supply for any damage or condition resulting from circumstances beyond our control, including any of the following:

- a. Acts of God, falling objects, explosions, or tire;
- b. Harmful fumes or foreign substances in the atmosphere, standing water or salt spray;
- c. Failure to apply a minimum dry film thickness of 0.7 mils of the Fluropon coil coatings to a properly pre-treated and primed substrate in accordance with our specifications and I instructions as outlined on our then-current published product data sheets;
- d. Improper treatment or defects in the substrate metal or in its fabrication;
- e. When roof is not uniformly insulated;
- f. Failure to store or install products coated with Fluropon in a way that allows for inadequate circulation. Condensation attributable to improper packaging, handling, shipping, processing and/or installation;
- g. Failures or damage resulting from edge corrosion or failure of the metal substrate;
- h. Development of an other conditions between the coating and the substrate which causes the coating to degrade or delaminate, including any failure or deficiency in the cleaning process or pretreatment;
- i. Contact with animals or animal waste;
- j. Mishandling material including abuse, alteration, modification, improper use, or storage contrary to our written instructions;
- k. Other circumstances or occurrences beyond Central LA Metal Supply's control.

No warranty is provided for Fluropon and Fluropon WXL on any substrate that is subjected to sea spray or installed on property located 1,500 or fewer feet from a salt-water environment.

If chrome free pretreatment is used, warranty for adhesion must be validated by sample testing of production material. Material must pass fifteen (15) minute boiling water/crosshatch adhesion will not tape off.

Panel material should be used within 60 days of purchase. Aging varies with the substrate, pretreatment and coatings, but in all cases will affect the coatings flexibility and subsequent performance. Storage conditions should be controlled to avoid potential forming and performance problems. Extreme changes in temperature, humidity levels and exposure to moisture can all have an adverse effect on material performance. Long storage times before forming may affect your warranty. The slow changes in properties over time are not a concern once the material is formed.

This warranty applies only to building parts installed on buildings within the Continental United States, Alaska and Canada. This warranty will automatically expire upon any change or transfer of ownership of the property on which the metal coated with Fluropon and Fluropon WXL is originally installed.